

15-inch Capacitive Touch Monitor



Product Features

- Industrial grade LCD panel, 24/7 continuous operation
- PCAP touch supports Wet & Glove Touch function
- Surface treatment AR / AF / AG optional (Mohs 7)
- IP65 front / IP40 back rating protection
- Full customization service available
- Durable mechanical design for harsh environments
- Optical Bonding function (customized option)
- Wide temperature design with high reliability
- Brightness upgradeable to 1,500 nits



Anti-Magnetic



Waterproof



Shock-Proof



Anti-Corrosion



Anti-Glare



Wide Temp.

Specifications

LCD Panel	
Screen Size	15"
IP Rating	IP65 front
Active Area (mm)	305.1 (H) × 229.1 (V)
Pixel Pitch (mm)	0.297× 0.297 [85 PPI]
Display Resolution (pixel)	1024(RGB) × 768 4:3 XGA
Display Type	a-Si TFT-LCD
Contrast Ratio	2500:1
Support Color	262K/16.2M 72% NTSC
Brightness	500 cd/m ²
Backlight	WLED / 70,000H
Viewing Angles (CR=10)	88/88/88/88 (Typ.)
Response Time(Typ.Tr+Td)	13/5ms
Touch Screen	
Touch Technology	Capacitive Multi-touch
Touch Interface	USB
Surface Treatment	AG/AR/AF Optional
Glass Thickness	2mm
Optical Bonding	Yes (Wacker AB adhesive)
Connectors	
Signal Connector	HDMI+VGA+DVI(DP Optional)
Power	
Power Input	DC 12V (9–36V Optional)
Output Power	≤20W
Operation / Mechanical	
Dimension (V×H×T) mm	337.1 × 276 × 42.8
Operating Temperature	-30 ~ 80°C
Storage Temperature	-40 ~ 85°C
Relative Humidity	10~90(%RH)(non-condensation)
Housing Material	Sheet metal + profiles
VESA Mounting	VESA 100×100
Weight	4kg
Warranty	
Warranty Period	1 Year

* Additional customized specifications available upon request.

Dimensions (Unit: mm)

