

15.3-inch Capacitive Touch Monitor



Product Features

- Industrial grade LCD panel, 24/7 continuous operation
- PCAP touch supports Wet & Glove Touch function
- Surface treatment AR / AF / AG optional (Mohs 7)
- IP65 rating protection
- Full customization service available
- Durable mechanical design for harsh environments
- Optical Bonding function (customized option)
- Wide temperature design with high reliability
- Brightness upgradeable to 1,500 nits



Anti-Magnetic



Waterproof



Shock-Proof



Anti-Corrosion



Anti-Glare



Wide Temp.

Specifications

LCD Panel	
Screen Size	15.3"
IP Rating	IP65
Active Area (mm)	374.8 (H) × 100.1 (V)
Display Resolution (pixel)	1280 × 370
Display Type	a-Si TFT-LCD
Contrast Ratio	1000:1
Support Color	16.7M
Brightness	500 cd/m ²
Backlight	LED / 30,000H
Viewing Angles (CR=10)	89/89/89/89 (L/R/U/D)
Response Time(Typ.Tr+Td)	18ms
Touch Screen	
Touch Technology	Capacitive Multi-touch
Touch Interface	USB
Surface Treatment	AG/AR/AF Optional
Optical Bonding	Yes (Wacker AB adhesive)
Glass Thickness	3mm
Connectors	
Signal Connector	HDMI(VGA/DVI/DP Optional)
Power	
Power Input	DC 12V (9~36V Optional)
Output Power	≤36W
Operation / Mechanical	
Dimension (V×H×T) mm	418 × 146.8 × 60
Operating Temperature	0 ~ 50°C
Storage Temperature	-20 ~ 65°C
Relative Humidity	10~90(%RH)(non-condensation)
Housing Material	Sheet metal + profiles
VESA Mounting	VESA 200×75
Weight	5kg
Warranty	
Warranty Period	1 Year

* Additional customized specifications available upon request.

Dimensions (Unit: mm)

