

17-inch Capacitive Touch Monitor



Product Features

- Industrial grade LCD panel, 24/7 continuous operation
- PCAP touch supports Wet & Glove Touch function
- Surface treatment AG Coating (Mohs 7)
- IIP65 front / IP40 back rating protection
- Durable mechanical design for harsh environments
- Optical Bonding function
- Wide temperature design with high reliability



Anti-Magnetic



Waterproof



Shock-Proof



Anti-Corrosion



Anti-Glare



Wide Temp.

Specifications

LCD Panel	
Screen Size	17"
IP Rating	IP65 front
Active Area (mm)	337.0 (H) × 270.0 (V)
Pixel Pitch (mm)	0.264× 0.264 [96 PPI]
Display Resolution (pixel)	1280(RGB) × 1024 5:4 SXGA
Display Type	a-Si TFT-LCD
Contrast Ratio	1000:1
Support Color	16.7M
Brightness	1000 cd/m ²
Backlight	WLED / 30,000H
Viewing Angles (CR=10)	85/85/80/80 (Typ.)
Response Time(Typ.Tr+Td)	20ms
Touch Screen	
Touch Technology	Capacitive Single-touch (Support glove and raining touch)
Touch Interface	USB
Surface Treatment	AG
Glass Thickness	2mm
Optical Bonding	Yes (Wacker AB adhesive)
Connectors	
Signal Connector	HDMI+VGA+DVI
Power	
Power Input	DC 24V
Output Power	≤36W
Parameter Current	1.5A
Standby Power	≤0.5W
Fan	
Outline Dimension	50 X 50 X 15 mm (2pcs)
Rated Speed	3600RPM ±10%
Max.Airflow	8.9 CFM
Operation / Mechanical	
Dimension (V×H×T) mm	380.3 × 318.0 × 53.5
Operating Temperature	-20 ~ 70°C
Storage Temperature	-20 ~ 70°C
Relative Humidity	10~90(%RH)(non-condensation)
Housing Material	Sheet metal + profiles
VESA Mounting	Customized
Weight	5.5kg
Warranty	
Warranty Period	1 Year

Dimensions (Unit: mm)

